

15T

15TR3-SLSA3-60


刚性值(μm / kef)

Φ P.218

平衡值(N)


Φ P.221

一体型 3°



■注意事项

- 刀具安装…插入刀具时,请务必将刀具插入比安全记号更深的位置。



BROTHER

TC-20A
TC-20B



壁厚



HEATROBO电磁 1200S
(HRD-01S-230AS)
电磁式加热器对应表

[○] 可加热 [×] 不可加热

型号	φD	φC	t	L	M	L1	φC1	φC2	H	h	Kg	N	S	省略图	
15TR3-SLSA 3-40	3	6	1.5	40	22	5.5	8.3	18	9	46	0.1	0.3	4.7	○	1
				60	42		10.4			66			9.3		2
15TR3-SLSA3.175-40	3.175	6.175	1.5	40	22	5.5	8.5	18	9	46	0.1	0.3	4.4	○	3
				60	42		10.6			66			8.8		4
15TR3-SLSA 4-40	4	7	1.5	40	22	5.5	9.3	18	12	46	0.1	0.3	3.6	○	5
				60	42		11.4			66			7.3		6
15TR3-SLSA 5-40	5	8	1.5	40	22	5.5	10.3	18	15	46	0.1	0.3	2.9	○	7
				60	42		12.4			66			5.9		8
15TR3-SLSA 6-60	6	9	1.5	60	42	5.5	13.4	18	18	66	0.1	0.4	4.9	○	9
				-SLRA 6-35	12		3			35			19.6		2.9
15TR3-SLRA 8-35	8	14	3	35	19.6	2.9	16.1	-	20	51	0.1	0.3	0.9	×	11
15TR3-SLRA10-35	10	16	3	35	19.6	2.9	18.1	-	20	51	0.1	0.4	0.8	×	12

S=1:3

φ3

15TR3-SLSA3-40

φ3.175

15TR3-SLSA3-60

φ3.175

15TR3-SLSA3.175-40

φ3.175

15TR3-SLSA3.175-60

φ4

15TR3-SLSA4-40

φ4

15TR3-SLSA4-60

φ5

15TR3-SLSA5-40

φ5

15TR3-SLSA5-60

φ6

15TR3-SLSA6-60

φ6

15TR3-SLRA6-35

φ8

15TR3-SLRA8-35

φ10

15TR3-SLRA10-35